


**Massiv**  
speichernd  
warm

**Holz**  
ökologisch  
gesund

**Mauer**  
homogen  
einfach



**DECLARATION OF PERFORMANCE - DoP**  
Nr. MHM Profiled aluminium nail 13/0801 25-02-05

**1. Unique identification code for the product type:**  
Profiled aluminium nail

**2. Type, batch or series number or other identifier of the building product**  
A "B" is pressed into the nail head of the MHM profiled aluminium nails for identification.

**3. Manufacturer's intended use or intended use of the building product**  
The MHM profiled aluminium nail is used to join softwoods. Its intended use includes joints for which requirements for mechanical strength and stability as well as safety in use, as defined in the essential requirements 1 and 4 of Council Directive 89/106/EEC, must be met.

**4. Name, registered trade name or registered trademark and manufacturer's contact address.**  
MHM Entwicklungs GmbH – Kemptener Str. 1 – 877749 Hawangen, Germany

**5. System or systems for the assessment and verification of the constancy of performance of the building product in accordance with Appendix V:**  
System 3

**6. In case of a Declaration of Performance concerning a building product for which a European Technical Assessment has been issued:**  
The Österreichisches Institut für Bautechnik (Austrian Institute for Construction Technology, ÖIB), Schenkenstraße 4, 1010 Vienna, Austria, has issued the following: European Technical Approval ETA – 13/0801 based on an EAD 130287-00-0603 "Profiled aluminium nail for use in timber structures" The manufacturer performs plant's own production controls according to System 3.

**7. Declared performance**

Essential features	Performance	
Dimensions	ETA-13/0801 Appendix 1	Nominal diameter 2.5 mm, nominal length 50 mm
Characteristic yield moment	ETA-13/0801 Appendix 2	$M_{y,k}$ 800 N
Characteristic withdrawal resistance parameter	ETA-13/0801 Appendix 2	$F_{ax,t,90^{\circ}}$ $50 \cdot 10^{-6} \cdot l_{ef} \cdot d \cdot \rho_k^2$ <sup>1)</sup>
Characteristic head pull-through resistance parameter	ETA-13/0801 Appendix 2	$F_{head,k}$ $100 \cdot 10^{-6} \cdot d_h^2 \cdot \rho_k^2$ <sup>1)</sup>
Characteristic tensile load capacity	ETA-13/0801 Appendix 2	$F_{tens,k}$ 1400 N/mm
Transverse elasticity modulus	ETA-13/0801 Appendix 2	$K_{ser}$ 300 N/mm
Characteristic load bearing capacity perpendicular to the nail axis	ETA-13/0801 Appendix 2	$F_{la,k}$ 400 N/mm
Durability against corrosion	ETA-13/0801 3.1.1	Service class 1 and 2 / C1,C2,C3 EN ISO 12944-2
Fire behaviour	ETA-13/0801 3.1.2	European classification A1

<sup>1)</sup>  $l_{ef}$ ...Length in the wooden part  $l_{ef} \geq 8 d$   
 $\rho_k$ ... Characteristic density of the wood in kg/m<sup>3</sup>

**8. The performance of the product in accordance with numbers 1 and 2 corresponds to the declared performance according to number 7. The manufacturer is solely responsible for the production of this Declaration of Performance in accordance with number 4.**

**Signed for the manufacturer and in the name of the manufacturer by:**  
Name and function

Josef Hundegger Managing Director

Hawangen, 06.02.25  
Place and date of issue

  
Signature

MHM Entwicklungs GmbH  
Kemptener Str. 1  
87749 Hawangen  
Deutschland

Tel.: +49 (0)8332 9233 2090  
E-Mail: info@massivholzmauer.de  
Web: www.massivholzmauer.de

Bankverbindung:  
Sparkasse Schwaben-Bodensee  
BIC: BYLA DE M1 MLM  
IBAN: DE70 7315 0000 0010 1570 48

Sitz der Gesellschaft: Hawangen  
Amtsgericht Kempten HRB 20923  
Geschäftsführer:  
Hans Hundegger, Josef Hundegger  
USt-IdNr.: DE 813 678 699